



PINE HALL BRICK

BUILD YOUR DREAMS.

2701 Shorefair Drive, Winston-Salem, NC 27105 | pinehallbrick.com | 1-800-334-8689

Product Features & Specifications

Rumbled Series Product Features & Colors

Features: Tumbled after firing for old worn out historical appearance

Colors: Red, Full Range, Cocoa, Autumn, Rose, Ironspot, Main Street (full range with white smears), Bluffs (cocoa with whitish tan coating) from Madison, NC Plant. Red, Full Range, Beale Street, Harvest, Canterra, Java, Siesta and Main Street (full range with white smears) from Fairmount, GA Plant.

Rumbled Series 2.25" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C902, Class SX, Type 1, Application PA and C67 for Freeze and Thaw. Units shall be standard 4" x 8" size having dimensions of 2 1/4" x 4" x 8", tumbled after firing, 8,000 psi minimum compressive strength and below 8% cold water absorption. Paver shall conform to Rumbled® Series [color] as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification].

Rumbled Series Heavy Vehicular 2.75" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C1272, Application PA and C67 for Freeze and Thaw. The units shall be standard 4" x 8" size having dimensions of 2 3/4" x 4" x 8", tumbled after firing for old worn out historical appearance, 10,000 psi minimum compressive strength, minimum breaking load of 475 lb/in and below 6% cold water absorption. Paver shall conform to Rumbled® Series [color] as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification].