



# PINE HALL BRICK

BUILD YOUR DREAMS.

2701 Shorefair Drive, Winston-Salem, NC 27105 | pinehallbrick.com | 1-800-334-8689

---

## Product Features & Specifications

### Square-Edge Series Product Features & Colors

Features: square edge brick pavers available in 4"X 8" and Modular Size

Colors: 4x8" available in Red, Full Range, Autumn, Cocoa, Rose, Dark Accent and Ironspot from Madison, NC Plant. Red, Full Range, Beale Street, Harvest, Canterra, Java, Siesta, Buff and Gray from Fairmount, GA Plant. Modular available in Red, Full Range and Cocoa from Madison, NC Plant and Red and Full Range from Fairmount, GA Plant.

### Square-Edge Series 2.25" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C902, Class SX, Type 1, Application PX and C67 for Freeze and Thaw. Units shall be standard 4" x 8" (or standard modular) size having dimensions of 2 1/4" x 4" x 8" (or 2 1/4" x 3 5/8" x 7 5/8"), square-edge on both sides, 8,000 psi minimum compressive strength and below 8% cold water absorption. Paver shall conform to Pathway [color] or Courtyard [color] as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification].

### Square-Edge Heavy Vehicular 2.75" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C1272, Application PA and C67 for Freeze and Thaw. Units shall be standard 4" x 8" size having dimensions of 2 3/4" x 4" x 8", tumbled after firing for old worn out historical appearance, 10,000 psi minimum compressive strength, minimum breaking load of 475 lb/in and below 6% cold water absorption. Paver shall conform to Pathway Series or Courtyard Series as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification].