



PINE HALL BRICK

BUILD YOUR DREAMS.

2701 Shorefair Drive, Winston-Salem, NC 27105 | pinehallbrick.com | 1-800-334-8689

Product Features & Specifications

Square-Edge Series Product Features & Colors

Features: square edge brick pavers available in 4"X 8" and Modular Size

Colors: 4x8" available in Red, Full Range, Beale St., Autumn, Cocoa, Rose, Dark Accent, Buff, Grey and Ironspot from Madison, NC Plant. Modular available in Red, Full Range and Cocoa from Madison, NC Plant.

Square-Edge Series 2.25" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C902, Class SX, Type 1, Application PX and C67 for Freeze and Thaw. Units shall be standard 4" x 8" (or standard modular) size having dimensions of 2 1/4" x 4" x 8" (or 2 1/4" x 3 5/8" x 7 5/8"), square-edge on both sides, 8,000 psi minimum compressive strength and below 8% cold water absorption. Paver shall conform to Pathway [color] as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification].

Square-Edge Heavy Vehicular 2.75" Product Specifications

Unit clay paver shall conform to the requirements of ASTM C1272, Application PA and C67 for Freeze and Thaw. Units shall be standard 4" x 8" size having dimensions of 2 3/4" x 4" x 8", 10,000 psi minimum compressive strength, minimum breaking load of 475 lb/in and below 6% cold water absorption. Paver shall conform to Pathway Series as manufactured by Pine Hall Brick Co., Inc., Winston-Salem, North Carolina and distributed by [party responsible for specification]. *(Note: Designer needs to emphasize proper paver spacing of 1/16" min to 3/16" max in written specs when specifying this paver in a heavy vehicular paving application. Expect chippage regardless.)*

Jan 2021

